(19) World Intellectual Property **Organization** International Bureau



(43) International Publication Date 14 April 2005 (14.04.2005)

PCT

(10) International Publication Number WO 2005/034241 A1

(51) International Patent Classification7: 27/148, 31/02

H01L 27/06,

(21) International Application Number:

PCT/IL2004/000915

(22) International Filing Date: 4 October 2004 (04.10.2004)

(25) Filing Language:

English


(26) Publication Language:

English

(30) Priority Data: 158345

9 October 2003 (09.10.2003)

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,



circuits in the detector whereby an exposed surface of the sensor elements forms a common first electrode towards which incident photons are directed, and an opposite unexposed surface thereof forms multiple second electrodes of opposite polarity to the first electrode each in registration with a corresponding sensor input.

